






# FR 790 SCC | Full Extension Progressive Action Drawer Slide




## Specifications

-  side mount
-  18.0 mm / 0.71 in.  
dynamic up to 68 kg / 150 lbs. (full extension)  
dynamic up to 53 kg / 120 lbs. (over extension)
-  solid synthetic rollers
-  stainless steel 1.4509 / 441
-  -25 °C to +80 °C  
-13 °F to +176 °F

## Characteristics

- high lateral stability
- cabinet and drawer profile with screw holes
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- compatible with regular extension drawer slide FR 1052 SCC
- available as heat-resistant version up to +110 °C (+230 °F) – load capacity 40 kg (90 lbs.) for over extension (drawer profile without screw holes)

## Dimensions



Length		Extension		Extension		Weight		Item No.	Item No.	Item No.
		full extension		over extension		per set		full extension	over extension	over extension heat-resistant
mm	inch	mm	inch	mm	inch	kg	lbs.			
350	13.78	335	13.19	410	16.14	1.62	3.57	7900	*	7970
400	15.75	385	15.16	460	18.11	1.81	3.99	7901	*	*
450	17.72	435	17.13	510	20.08	2.04	4.49	7902	*	7972
500	19.69	485	19.09	560	22.05	2.28	5.02	7903	*	7973
550	21.65	535	21.06	610	24.02	2.49	5.50	7904	7924	7974
600	23.62	585	23.03	660	25.98	2.73	6.01	7905	*	7975
650	25.59	635	25.00	710	27.95	2.98	6.57	7906	7926	*
700	27.56	685	26.97	760	29.92	3.18	7.00	7907	*	*
750	29.53	735	28.94	810	31.89	*	*	*	*	*

Packing Unit – Sets per Box, all Lengths: 5

\* on request