







FR 795 SCC OE

Over Extension Progressive Action Drawer Slide



Specifications

-  side mount
-  18.0 mm / 0.71 in.
-  dynamic up to 60 kg / 132 lbs.
-  solid synthetic rollers
-  stainless steel 1.4509 / 441
-  -25 °C to +80 °C
-13 °F to +176 °F


Characteristics

- high lateral stability
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- compatible with regular extension drawer slide FR 1052 SCC
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally

Mounting Type

- cabinet and drawer profile with screw holes

Dimensions



Length		Extension		Weight		Item No.	Item No.
				per set		PU 1	PU 2
mm	inch	mm	inch	kg	lbs.		
300	11.81	335	13.19	1.34	2.96	▶ 70330	▶ 70330GV
350	13.78	385	15.16	1.50	3.31	▶ 70331	▶ 70331GV
400	15.75	460	18.11	1.68	3.71	▶ 70332	▶ 70332GV
450	17.72	510	20.08	1.93	4.26	▶ 70333	▶ 70333GV
500	19.69	560	22.05	2.16	4.76	▶ 70334	▶ 70334GV
550	21.65	610	24.02	2.39	5.26	▶ 70335	▶ 70335GV
600	23.62	660	25.98	2.62	5.78	▶ 70336	▶ 70336GV
650	25.59	710	27.95	2.87	6.32	▶ 70337	▶ 70337GV
700	27.56	760	29.92	3.10	6.83	▶ 70338	▶ 70338GV
750	29.53	810	31.89	3.34	7.36	▶ 70339	▶ 70339GV

Packing Unit

PU 1 – Sets assembled per Box, all Lengths: 5

PU 2 – 50 Sets, all 6 profiles individually packaged, 10 boxes

(4 x 25 cabinet profiles LEFT/RIGHT, 4 x 25 middle profiles LEFT/RIGHT, 2 x 50 drawer profiles LEFT/RIGHT)

▶ in stock