



Specifications

- side mount
- 18.0 mm / 0.71 in.
- dynamic up to 70 kg / 154 lbs.
- solid synthetic rollers
- stainless steel 1.4509 / 441
- 25 °C to +80 °C
-13 °F to +176 °F


Characteristics

- high lateral stability
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- compatible with regular extension drawer slide FR 1052 SCC
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally

Mounting Type

- cabinet and drawer profile with screw holes

Dimensions



Length		Extension		Weight		Item No.	Item No.
				per set		PU 1	PU 2
mm	inch	mm	inch	kg	lbs.		
300	11.81	285	11.22	1.33	2.93	70320	70320GV
350	13.78	335	13.19	1.49	3.28	70321	70321GV
400	15.75	385	15.16	1.67	3.68	70322	70322GV
450	17.72	435	17.13	1.92	4.23	70323	70323GV
500	19.69	485	19.09	2.15	4.73	70324	70324GV
550	21.65	535	21.06	2.37	5.23	70325	70325GV
600	23.62	585	23.03	2.61	5.75	70326	70326GV
650	25.59	635	25.00	2.85	6.29	70327	70327GV
700	27.56	685	26.97	3.08	6.80	70328	70328GV
750	29.53	735	28.94	3.33	7.33	70329	70329GV

Packing Unit

PU 1 – Sets assembled per Box, all Lengths: 5

PU 2 – 50 Sets, all 6 profiles individually packaged, 10 boxes

(4 x 25 cabinet profiles LEFT/RIGHT, 4 x 25 middle profiles LEFT/RIGHT, 2 x 50 drawer profiles LEFT/RIGHT)