







FR 795 SCC OE

Over Extension Progressive Action Drawer Slide



Specifications

-  side mount
-  18.0 mm / 0.71 in.
-  dynamic up to 60 kg / 132 lbs.
-  solid synthetic rollers
-  stainless steel 1.4509 / 441
-  -25 °C to +80 °C
-13 °F to +176 °F


Characteristics

- high lateral stability
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- compatible with regular extension drawer slide FR 1052 SCC
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally

Mounting Type

- cabinet and drawer profile with screw holes

Dimensions



Length		Extension		Weight		Item No.	Item No.
				per set		PU 1	PU 2
mm	inch	mm	inch	kg	lbs.		
300	11.81	335	13.19	1.34	2.96	70330	70330GV
350	13.78	385	15.16	1.50	3.31	70331	70331GV
400	15.75	460	18.11	1.68	3.71	70332	70332GV
450	17.72	510	20.08	1.93	4.26	70333	70333GV
500	19.69	560	22.05	2.16	4.76	70334	70334GV
550	21.65	610	24.02	2.39	5.26	70335	70335GV
600	23.62	660	25.98	2.62	5.78	70336	70336GV
650	25.59	710	27.95	2.87	6.32	70337	70337GV
700	27.56	760	29.92	3.10	6.83	70338	70338GV
750	29.53	810	31.89	3.34	7.36	70339	70339GV

Packing Unit

PU 1 – Sets assembled per Box, all Lengths: 5

PU 2 – 50 Sets, all 6 profiles individually packaged, 10 boxes

(4 x 25 cabinet profiles LEFT/RIGHT, 4 x 25 middle profiles LEFT/RIGHT, 2 x 50 drawer profiles LEFT/RIGHT)