







FR 795 SCC OE SMT

Over Extension Progressive Action Drawer Slide



Specifications

-  side mount
-  18.0 mm / 0.71 in.
-  dynamic up to 60 kg / 132 lbs.
-  solid synthetic rollers
-  stainless steel 1.4509 / 441
-  -25 °C to +80 °C
-13 °F to +176 °F


Characteristics

- high lateral stability
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- compatible with regular extension drawer slide FR 1052 SCC SMT
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally

Mounting Type

- cabinet profile with bayonet mounting tabs and safety nose
- drawer profile without screw holes
- tool-less quick assembly of the cabinet profile

Dimensions



Length		Extension		Weight		Item No.	Item No.
				per set		PU 1	PU 2
mm	inch	mm	inch	kg	lbs.		
300	11.81	335	13.19	1.38	3.04	70450	70450GV
350	13.78	385	15.16	1.46	3.22	70451	70451GV
400	15.75	460	18.11	1.69	3.73	70452	70452GV
450	17.72	510	20.08	1.93	4.26	70453	70453GV
500	19.69	560	22.05	2.16	4.76	70454	70454GV
550	21.65	610	24.02	2.40	5.28	70455	70455GV
600	23.62	660	25.98	2.64	5.82	70456	70456GV
650	25.59	710	27.95	2.87	6.33	70457	70457GV
700	27.56	760	29.92	3.11	6.86	70458	70458GV
750	29.53	810	31.89	3.37	7.43	70459	70459GV

Packing Unit

PU 1 – Sets assembled per Box, all Lengths: 5

PU 2 – 50 Sets, all 6 profiles individually packaged, 10 boxes

(4 x 25 cabinet profiles LEFT/RIGHT, 4 x 25 middle profiles LEFT/RIGHT, 2 x 50 drawer profiles LEFT/RIGHT)