







FR 795 SCC SMT

Full Extension Progressive Action Drawer Slide



Specifications

-  side mount
-  18.0 mm / 0.71 in.
-  dynamic up to 70 kg / 154 lbs.
-  solid synthetic rollers
-  stainless steel 1.4509 / 441
-  -25 °C to +80 °C
-13 °F to +176 °F


Characteristics

- high lateral stability
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- compatible with regular extension drawer slide FR 1052 SCC SMT
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally

Mounting Type

- cabinet profile with bayonet mounting tabs and safety nose
- drawer profile without screw holes
- tool-less quick assembly of the cabinet profile

Dimensions



Length		Extension		Weight		Item No.	Item No.
				per set		PU 1	PU 2
mm	inch	mm	inch	kg	lbs.		
300	11.81	285	11.22	1.37	3.01	70440	70440GV
350	13.78	335	13.19	1.44	3.19	70441	70441GV
400	15.75	385	15.16	1.68	3.70	70442	70442GV
450	17.72	435	17.13	1.92	4.23	70443	70443GV
500	19.69	485	19.09	2.14	4.73	70444	70444GV
550	21.65	535	21.06	2.38	5.25	70445	70445GV
600	23.62	585	23.03	2.62	5.79	70446	70446GV
650	25.59	635	25.00	2.86	6.30	70447	70447GV
700	27.56	685	26.97	3.10	6.83	70448	70448GV
750	29.53	735	28.94	3.36	7.40	70449	70449GV

Packing Unit

PU 1 – Sets assembled per Box, all Lengths: 5

PU 2 – 50 Sets, all 6 profiles individually packaged, 10 boxes

(4 x 25 cabinet profiles LEFT/RIGHT, 4 x 25 middle profiles LEFT/RIGHT, 2 x 50 drawer profiles LEFT/RIGHT)