







# FR 796 SCC OE

Over Extension Progressive Action Drawer Slide



## Specifications

-  bottom mount
-  18.0 mm / 0.71 in.
-  dynamic up to 60 kg / 132 lbs.
-  solid synthetic rollers
-  stainless steel 1.4509 / 441
-  -25 °C to +80 °C  
-13 °F to +176 °F


## Characteristics

- high lateral stability
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally

## Mounting Type

- cabinet and drawer profile with screw holes

## Dimensions



Length		Extension		Weight		Item No.	Item No.
				per set		PU 1	PU 2
mm	inch	mm	inch	kg	lbs.		
300	11.81	335	13.19	1.46	3.22	70490	70490GV
350	13.78	385	15.16	1.63	3.60	70491	70491GV
400	15.75	460	18.11	1.83	4.03	70492	70492GV
450	17.72	510	20.08	2.09	4.62	70493	70493GV
500	19.69	560	22.05	2.34	5.16	70494	70494GV
550	21.65	610	24.02	2.58	5.69	70495	70495GV
600	23.62	660	25.98	2.84	6.25	70496	70496GV
650	25.59	710	27.95	3.10	6.82	70497	70497GV
700	27.56	760	29.92	3.35	7.37	70498	70498GV
750	29.53	810	31.89	3.60	7.94	70499	70499GV

### Packing Unit

**PU 1 – Sets assembled per Box, all Lengths: 5**

**PU 2 – 50 Sets**, all 6 profiles individually packaged, 10 boxes

(4 x 25 cabinet profiles LEFT/RIGHT, 4 x 25 middle profiles LEFT/RIGHT, 2 x 50 drawer profiles LEFT/RIGHT)